



8 Adapter (1-16 Fiber) Heavy Duty Waterproof Outdoor IP65 Rated Wall Mount Mount Fiber Optic Enclosure with Wire Management, Removable 8 Fiber Splice Tray, Splice Sleeves, and Locking Door with Key

General Description

This box is used as a termination point for the feeder cable to connect with drop cable in FTTx communication network system. It integrates fiber splicing, splitting, distribution, storage and cable connection in one unit. Meanwhile, it provides solid protection and management for the FTTx network building.

Features

- ◆ Total enclosed structure
- ◆ Protects and manages cable effectively
- ◆ Secured with anti-theft locking mechanism
- ◆ Standard size, light weight
- ◆ High quality Plastic material
- ◆ Good properties of dust, and moisture proofing, IP65
- ◆ Clamping for feeder cable and drop cable, fiber splicing, fixation, storage, distribution...etc all in one
- ◆ Suitable for SC and LC duplex adaptor and pigtail
- ◆ Easy to operate
- ◆ Wall and pole mountable (accessories optional)
- ◆ Suitable for both outdoor and indoor use

Application

- Telecommunication subscriber loop
- Fiber to the home (FTTH)
- LAN/WAN

Technical Data

Work Temperature	-40 °C ~ +85 °C
Relative Humidity	≤ 85% (+30 °C)
Atmospheric Pressure	70Kpa-106Kpa
Withstand Voltage	The grounding device is insulated with the Termination box, IR < 1000m Ω/500V (direct current) Between the grounding device and the box body, the withstand voltage is over 3000V/Min, no breakdown and flashover. U < 3000V (direct current) nt

Dimensions

