



**12 - 24 Fiber Outdoor IP68 Rated Aerial Horizontal / Wall Mountable
Fiber Optic Slitter / Splice Enclosure with Splice Sleeves, Splice Tray,
and Mounting Hardware**

Part # QT-OAWM-SSE-24F-IP68



Overview

Our QuickTreX® 12 - 24 Fiber Outdoor IP65 Rated Aerial Horizontal / Wall Mountable Fiber Optic Slitter / Splice Enclosure with Splice Sleeves, Splice Tray, and Mounting Hardware is perfect for interconnectivity and termination of optical fibers in outdoor overhead distribution locations and for wall mount locations. Its made of high strength PP plastics to provide heavy duty UV and waterproof protection of your fiber optic connectors. It's also corrosion and aging resistant. It includes one 12/24 fiber hinged splice tray and is designed to house an optional PLC splitter cassette. It offers a high quality sealing gasket to help seal out moisture and dust. This enclosure has a clamp stile door and is designed to be aerially on a guy wire and can also be wall mounted. It includes aerial mounting brackets, 16 splice sleeves, electrical tape, hose/cable clamps, and zip ties.

SPECIFICATIONS

Dimensions:	11.42W" 7.08H x 4.33" D
Weight:	4 lbs
Fiber Capacity:	12-24 Fibers
Spice Trays:	(1) 12/24 Fiber
Material:	High Strength PP Plastic
IP Rating:	IP68
Color:	Black
Cable Entry / Exit:	2 x 8-20mm and 8 x 5-14mm
Work Temperature:	40 °C ~ +75 °C
Relative Humidity:	≤ 85%
Atmospheric Pressure:	70Kpa ~ 106Kpa
Standard:	YC/T814.1-2004
Impact:	1m/1kg Steel Ball/ three times
Bending:	150N/±45°/10 cycles
Torsion:	50N.m/+90°/10 cycles
Insulation Resistance:	2x10⁴MΩ/500V
Compression Strength:	15kv/1min/10mA
ISO9001 Manufacturing	

INCLUDES

- Aerial Hanging Brackets**
- (1) 12/24 Fiber Splice Tray**
- 16 Splice Sleeves**
- 6 Hose/Cable Clamps**
- Zip Ties**
- PVC Electrical Tape**



DIMENSIONS

