

# QUICKTREX® CAT 5E SHIELDED PLENUM CUSTOM ETHERNET PATCH CABLE

# BUILD SPECIFICATIONS

REV	ECR	DESCRIPTION	BY	DATE	CHECKED
Α	-	INITIAL RELEASE	T.D.	07/20/2018	T.D.


## MADE IN THE USA

NOTES: UNLESS OTHERWISE SPECIFIED


- 1. MATERIALS AND COMPONENTS ARE RoHS/REACH COMPLIANT.
- 2. CONNECTORS MEET THE REQUIREMENTS OF ANSI/TIA 568-C.2.
- 3. CABLE ASSEMBLIES ARE CUSTOM MADE IN THE USA AND MANUFACTURED TO QUICKTREX STANDARDS.
- WIRING CONFIGURATION: 568B STRAIGHT (STANDARD), 568A ALTERNATE, OR STANDARD CROSS-OVER.
- TESTING: FLUKE TESTED & CERTIFIED INCLUDING: CONTINUITY, SHORTS, WIRE MAPPING, NEXT (NEAR END CROSSTALK), AND RETURN LOSS.
- 6. EACH CABLE WILL INCLUDE LABEL WITH QUICKTREX PART NUMBER AND INDIVIDUAL SERIAL NUMBER. OPTIONAL CUSTOM LABEL IS OFFERED ON ONE END OR BOTH.
- 7. INCLUDES RJ45 SLIM SNAGLESS STRAIN RELIEF BOOTS
- 8. COLOR OPTIONS: GRAY
- 9. ISO9001 CERTIFIED MANUFACTURING.

#### STRAIN RELIEF BOOTS

**RJ45 SLIM SNAGLESS BOOT** 




### Length Measured Tip To Tip + or - 1" OPTIONS 6" THROUGH 250'



Insulation

#### CABLE SPECS:

- CONDUCTOR: F/UTP 24 AWG PURE STRANDED COPPER
- OVERALL METAL FOIL SCREEN WITH DRAIN WIRE
- CABLE: (4) TWISTED PAIRS
- JACKET: PLENUM LOW SMOKE FLAME RETARDANT PVC
- OVERALL CABLE DIAMETER: 5.7± 0.2 mm
- OPERATING ENVIRONMENT: -20°C TO +75°C
- SWEEP FREQUENCY UP TO 350 MHz.



#### MODULAR PLUG SPECS:

- PLUG BODY: CLEAR POLYCARBONATE, UL 94-2
- CONTACTS: BRASS/PHOSPHOR BRONZE, 50U GOLD PLATING
- SHELL: BRASS

### **PINOUT OPTIONS**

WIRING CONFIGURATION 568B STRAIGHT  STANDARD				WIRING CONFIGURATION 568A			
PIN	COLOR CODE	PIN		PIN	COLOR CODE	PIN	
1	WHITE/ORANGE	1		1	WHITE/GREEN	1	
2	ORANGE	2		2	GREEN	2	
3	WHITE/GREEN	3		3	WHITE/ORANGE	3	
4	BLUE	4		4	BLUE	4	
5	WHITE/BLUE	5		5	WHITE/BLUE	5	
6	GREEN	6		6	ORANGE	6	
7	WHITE/BROWN	7		7	WHITE/BROWN	7	
8	BROWN	8		8	BROWN	8	

CROSS-OVER						
PIN	COLOR CODE					
1	WHITE/ORANGE	WHITE/GREEN	1			
2	ORANGE	GREEN	2			
3	WHITE/GREEN	WHITE/ORANGE	3			
4	BLUE	WHITE/BROWN	4			
5	WHITE/BLUE	BROWN	5			
6	GREEN	ORANGE	6			
7	WHITE/BROWN	BLUE	7			
8	BROWN	WHITE/BLUE	8			

Mylar

WIRING CONFIGURATION

DESCRIPTION: RJ45 / RJ45 CAT5E SHIELDED PLENUM PATCH CORD								
DRAWN	DRAWN T. J. 07/20/2020			Purchase at				
BY:	1.0.	0112012020	LANshack					
APVD	T. D.	07/20/2018						
BY: 0772072010			Sales@LANshack.com   888-568-1230					
DIMENSIONS: METRIC [IMPERIAL]			TITLE:CAT 5E SHIELDED PLENUM RATED PREMIUM CUSTOM ETHERNET PATCH CABLE - MADE IN THE USA BY QUICKTREX®					
PROPRIETAR	Y AND CONF	IDENTIAL	SIZE	E PART NUMBER		REV		
THIS DOCUM	Y INFORMAT	ION OF	Α	053PLN-XX-XX		Α		
LANSHACK. NOT TO BE USED, COPIED, OR DISCLOSED WITHOUT WRITTEN PERMISSION. ALL RIGHTS RESERVED.			SCALE: NOT TO SCALE SHEET 1 0			OF 1		