



MATERIAL

PANEL : SPCC BLACK POWDER PAINTING COAT FINISH
 PANEL HOUSING : HIGH-IMPACT 94V-0 PLASTIC
 CABLE MANAGER : SPCC BLACK POWDER PAINTING COAT FINISH
 IDC PLASTIC : POLYCARBONATE 94V-0 PLASTIC
 IDC CONTACT : PHOSPHOR BRONZE TIN PLATED
 SPRING WIRE :PHOSPHOR BRONZE WITH 50U" GOLD PLATED ON CONTACT AREA

FEATURES

Terminates 26~23 AWG Solid Conductors
 Termination Type: 110 Punchdown

ENVIRONMENTAL CONDITIONS:

Storage Temperature: -40 ~ +70 °C
 Operating Temperature: -10 ~ +60 °C

MADE IN TAIWAN

TAA COMPLIANT



Scale		1:4		All Copy Rights Reserved	
3rd Angle Projection				P/N QT-110PL248-6B	
Unit		mm		Title QuickTreX® 24 Port Cat 6 Ethernet Patch Panel A	
Date		2016/07/27			
Tolerance					
~20	~50	~150	150~	ANGLE	Drawn by
±0.2	±0.4	0.5	±1.5	±2°	Checked by
				Roger	