									REV	ECR	DESCRIPTIO	N		BY	DATE	CHECKED		
CAT 6A SHIELDED CUSTOM PATCH CABLE									А	-	INITIAL RELE	ASE		T.D.	07/20/2018	T.D.		
BUILD SPECIFICATIONS											R 4			T II	-	\square		
OUICKTREX [®] MADE IN THE USA															SA			
- (NOTES: UNLE	ESS OTHERWISE SP	ECIFIED															
1. MATERIALS AND CO		6. EACH CABLE WILL INCLUDE LABEL WITH QUICKTREX PART NUMBER AND INDIVIDUAL SERIAL NUMBER. OPTIONAL LABEL IS OFFERED ON ONE END																
2. CONNECTORS MEET THE REQUIREMENTS OF ANSI/TIA 568-C.2.						OR BOTH					STRAIN RELIEF BOOTS							
 CABLE ASSEMBLIES ARE CUSTOM MADE IN THE USA AND MANUFACTURED TO QUICKTREX STANDARDS. 						7. EACH CABLE INCLUDES SLIM SNAGGLES BOOT												
 WIRING CONFIGURATION: 568B STRAIGHT (STANDARD), 568A ALTERNATE, OR 568B CROSS-OVER. 						8. COLOR OPTIONS: RAY, BLUE, BLACK, GREEN, RED, ORANGE, PURPLE, WHITE, AND YELLOW												
5. TESTING: FLUKE TESTED & CERTIFIED INCLUDING: CONTINUITY, SHORTS, WIRE MAPPING, NEXT (NEAR END CROSSTALK), AND RETURN LOSS. 9. ISO9001 CERTIFIED M							NUFACT	TURING]		
COMPONENT CERT																		
Length Measured Tip To Tip + or - 1" OPTIONS 6" THROUGH 250'																		
															7			
	D PART#	OPTIONAL				OPT	IONAL		UT		<u> </u>	P2				_ `		
	SERIAL #	# OPTIONAL CUSTOM LABEL		_0(_		LA	IONAL STOM ABEL		nll		J'	ΓZ						
						ak												
			F	PIN 8 —														
	ORG]		П									
																(
 INSULATION: POOPAOOPUQYÁUUŠYÓVP 								WHT/ ORG	\mathcal{Y}]	ΛHL	IH J		
CABLE: (4) TWISTED PAIRS SHIELD: AN ALUMINUM POLYESTI		GRN BRN () PIN 1																
(100% COVERAGE) WITH 7 ENDS OF 34 AWG TINNED COPPER										/								
DRAIN WIRE: IN CONTACT WITH THE METALIZED SURFACE SHALL BE APPLIED OVER THE CABLE CORE										/ M	ODULAR PL	UG SPECS:						
JACKET: RISER POLYVINYL CHLORIDE PVC OVERALL CABLE DIAMETER: 0.228" NOM.										•	PLUG BOD	Y: CLEAR POI	LYCARBO	ONATE	UL 94-VO			
OPERATING ENVIRONMENT: -20°C TO +75°C LOAD BAR: BLACK POLYCARBONATE, UL 94-VO																		
GROMMET: BLACK POLYCARBONATE, UL 94-VO																		
		CONTACTS: COPPER ALLOY, SELECTIVE GOLD PLATING SHIELD: COPPER ALLOY, NICKEL PLATE																
WIRING CONFIGURATION 568B STRAIGHT		G CONFIGURATION 5			WIRING CON	FIGURATION												
STANDARD	ουαΑ		568B CRO				DESCRIPTION: RJ45 SHIELDED/ RJ45 SHIELDED CAT6A PATCH CORD											
PIN COLOR CODE PIN	PIN	COLOR CODE	PIN	PIN	COLO	R CODE	PIN	DRAV	VN T. J.	07/20/2	2020	Purchase	at					
1 WHITE&ORANGE 1	1	WHITE&GREEN	1	1	WHITE/ORANGE		<u> </u>	BY:	I. J.	01/20/2	.020		NS	h				
2 ORANGE 2	2	GREEN	2	2		GREEN	2	APV	I.D.	. 07/20/2	2018	Sales@LANs				30		
3 WHITE&GREEN 3 4 BLUE 4	3	WHITE&ORANGE BLUE	3	3	WHITE/GREEN BLUE	WHITE/ORANGE		BY:			тіті							
4 BLUE 4 5 WHITE&BLUE 5	5	WHITE&BLUE	<u>4</u> 5	4	WHITE/BLUE	ME			METRIC [IMPERIAL] PA			CAT 6A 10G SHIELDED PREMIUM CUSTOM ETHERNET ATCH CABLE - MADE IN THE USA BY QUICKTREX®						
6 GREEN 6	6	ORANGE	6	6	GREEN	ORANGE	6		ETARY AND CO							REV		
7 WHITE&BROWN 7	7	WHITE&BROWN	7	7	WHITE/BROWN	HITE/BROWN BLUE 7 PROPRI LANSHA			IS DOCUMENT CONTAINS OPRIETARY INFORMATION OF NSHACK. NOT TO BE USED, COPIED, OR			05XHR-C6A-XX-XX				A		
8 BROWN 8	8	BROWN	8	8	BROWN	WHITE/BLUE	8	DISCLOS	SED WITHOUT			SCALE: NOT T	O SCALE		SHEET	1 OF 1		