


CAT 6A SHIELDED PLENUM CUSTOM PATCH CABLE **BUILD SPECIFICATIONS**

REV	ECR	DESCRIPTION	BY	DATE	CHECKED
Α	-	INITIAL RELEASE	T.D.	07/20/2018	T.D.

MADE IN THE USA

NOTES: UNLESS OTHERWISE SPECIFIED


- 1. MATERIALS AND COMPONENTS ARE RoHS/REACH COMPLIANT.
- 2. CONNECTORS MEET THE REQUIREMENTS OF ANSI/TIA 568-C.2.
- 3. CABLE ASSEMBLIES ARE CUSTOM MADE IN THE USA AND MANUFACTURED TO QUICKTREX STANDARDS.
- 4. WIRING CONFIGURATION: 568B STRAIGHT (STANDARD), 568A ALTERNATE. OR 568B CROSS-OVER.
- 5. TESTING: FLUKE TESTED INCLUDING 100% CONTINUITY, SHORTS, WIRE MAPPING, NEXT, RETURN LOSS & IMPEDANCE TEST.
- 6. EACH CABLE WILL INCLUDE LABEL WITH QUICKTREX PART NUMBER AND INDIVIDUAL SERIAL NUMBER. OPTIONAL LABEL IS OFFERED ON ONE END OR BOTH
- 7. EACH CABLE INCLUDES SLIM SNAGGLES BOOT
- 8. COLOR OPTIONS: BLUE AND GREY
- 9. ISO9001 CERTIFIED MANUFACTURING



RJ45 SLIM SNAGLESS BOOT

P2

Length Measured Tip To Tip + or - 1" OPTIONS 6" THROUGH 250' P1







Filler

Insulation







CABLE SPECS:

- CONDUCTOR: 23 AWG PURE SOLID COPPER WITH CROSS FILLER
- OVERALL METAL FOIL SCREEN WITH DRAIN WIRE
- INSULATION: FLUORINATED ETHYLENE PROPYLENE 1.10 ± 0.02 mm
- CABLE: (4) TWISTED PAIRS
- SHIELD: MYLAR TAPE 100 % COVERAGE
- DRAIN WIRE: 24AWG SOLID TINNED COPPER
- JACKET: LOW SMOKE FLAME RETARDANT POLYVINYL CHLORIDE
- OVERALL CABLE DIAMETER: 7.00± 0.2 mm
- OPERATING ENVIRONMENT: -20°C TO +60°C
- SWEEP FREQUENCY UP TO 650 MHz.

MODULAR PLUG SPECS:

PIN 8

PIN 1

Drain Wire

Jacket

Mylar

- PLUG BODY: CLEAR POLYCARBONATE, UL 94-VO
- LOAD BAR: BLACK POLYCARBONATE, UL 94-VO
- WIRE ALIGNER: CLEAR POLYCARBONATE, UL 94-VO
- GROMMET: BLACK POLYCARBONATE, UL 94-VO
- CONTACTS: COPPER ALLOY, SELECTIVE GOLD

DESCRIPTION: R M5 SHIELDED/R M5 SHIELDED PLENLIM CAT64 PATCH CORD

- PLATING SHIELD: COPPER ALLOY, NICKEL PLATE

PINOUT OPTIONS

STANDARD					
PIN	COLOR CODE	PIN			
1	WHITE&ORANGE	1			
2	ORANGE	2			
3	WHITE&GREEN	3			
4	BLUE	4			
5	WHITE&BLUE	5			
6	GREEN	6			
7	WHITE&BROWN	7			
8	BROWN	8			

WIRING CONFIGURATION 568B STRAIGHT

WIRING CONFIGURATION 568A					
PIN	COLOR CODE	PIN			
1	WHITE&GREEN	1			
2	GREEN	2			
3	WHITE&ORANGE	3			
4	BLUE	4			
5	WHITE&BLUE	5			
6	ORANGE	6			
7	WHITE&BROWN	7			
8	BROWN	8			

	568B CROSS-OVER					
PIN	COLOR CODE					
1	WHITE/ORANGE	WHITE/GREEN	1			
2	ORANGE	GREEN	2			
3	WHITE/GREEN	WHITE/ORANGE	3			
4	BLUE	WHITE/BROWN	4			
5	WHITE/BLUE	BROWN	5			
6	GREEN	ORANGE	6			
7	WHITE/BROWN	BLUE	7			
8	BROWN	WHITE/BLUE	8			

WIRING CONFIGURATION

	L	DESCRIPTION. NJ43 SHIELDED/ NJ43 SHIELDED FLENOW CATOA FATCH COND					
	DRAWN	T. J.	07/20/2020		Purchase at		
	BY:				LANSh	201	
	APVD	T. D.	07/20/2018				
	BY:			Sales@LANshack.com 888-568-1230			
	DIMENSIONS: METRIC [IMPERIAL]			TITLE: CAT 6A 10G SHIELDED PLENUM RATED CUSTOM ETHERNET PATCH CABLE - MADE IN THE USA BY QUICKTREX®			
	PROPRIETARY AND CONFIDENTIAL			SIZE	PART NUMBER		REV
	THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION OF LANSHACK. NOT TO BE USED, COPIED, OR DISCLOSED WITHOUT WRITTEN PERMISSION. ALL RIGHTS RESERVED.			Α	05XHP-C6A-XX-XX		Α
					SCALE: NOT TO SCALE	SHEET 1	OF 1