








**QuickTrex Custom Tactical Neutrik OpticalCON & FIBERFOX Fiber Optic Assemblies  
Optional Deployable Schill Reels**

Reel SKU	Main Features and Specifications
<p align="center"><b>GT 310</b></p> 	<p>Unbreakable synthetic rubber &amp; heavy-duty steel construction, high-quality fittings, and spool brake.</p> <p align="center">Flange Height: 310 mm / 12.2 in Core Diameter: 170 mm / 6.69 in Spool Width: 132 mm / 1.5 in Weight: 1.78 kg / 3.92 lbs</p>
<p align="center"><b>GT 380</b></p> 	<p>Unbreakable synthetic rubber &amp; heavy-duty steel construction, high-quality fittings, and spool brake.</p> <p align="center">Flange Height: 380 mm / 14.96 in Core Diameter: 236 mm / 9.29 in Spool Width: 182 mm / 7.17 in Weight: 4.25kg / 9.37 lbs</p>
<p align="center"><b>GT 450</b></p> 	<p>Unbreakable synthetic rubber &amp; heavy-duty steel construction, high-quality fittings, and spool brake.</p> <p align="center">Flange Height: 445 mm / 17.52 in Core Diameter: 296 mm / 11.65 in Spool Width: 187 mm / 7.36 in Weight: 5.1 kg / 11.3 lbs</p>
<p align="center"><b>HT 485</b></p> 	<p>Heavy-duty steel construction, high-quality fittings, spool brake, and folding crank.</p> <p align="center">Flange Height: 460 mm / 18.11 in Core Diameter: 178 mm / 7.01 in Spool Width: 210 mm / 8.27 in Weight: 7.63 kg / 16.82 lbs</p>
<p align="center"><b>SK 4812</b></p> 	<p>Industrial-duty steel frame &amp; drum flanges, glassfiber-reinforced polycarbonate core, stackable, high-quality fittings, spool brake, folding crank, blank hub cover for you own modifications, and available with optional wheels heavy-duty dolly.</p> <p align="center">Flange Height: 460 mm / 18.11 in Core Diameter: 240 mm / 9.4 in Spool Width: 336 mm / 13.23 in Weight: 17.90 kg / 39.46 lbs</p>
<p align="center"><b>SK 4813</b></p> 	<p>Industrial-duty steel frame &amp; drum flanges, glassfiber-reinforced polycarbonate core, stackable, high-quality fittings, spool brake, folding crank, blank hub cover for you own modifications, and available with optional wheels heavy-duty dolly.</p> <p align="center">Flange Height: 460 mm / 18.11 in Core Diameter: 240 mm / 9.4 in Spool Width: 504 mm / 19.84 in Weight: 17.90 kg / 39.46 lbs</p>
<p align="center"><b>Optional</b> Caster Wheels for SK Reels</p> 	<p align="center"><b>Optional</b> Dolly for SK Reels</p> 