



Category 6 W/ Messenger Flooded Polyethylene Jacket

Made in the USA

Part No.: **CAT6ENP4DBFMSGR**

Applications

Supports all category 6 applications including Ethernet 100BASE-TX, 100BASE-VG and 155 ATM. Particularly suited for high bandwidth applications such as 622 ATM, Wideband, Ethernet 1000BASE-T and emerging applications with anticipated data rates to 3.2 Gbps.

Construction Details:

No. 23 AWG solid bare copper conductor insulated with polyethylene. Two colored mated insulated conductors twisted together to form a pair and four pairs assembled to form a core. The core is flooded with a water resistant flooding compound and has a polyethylene jacket with an 0.045" steel messenger.

Color Code:

| Pair | Color Code |
|------|-------------------|
| 1 | Blue with White |
| 2 | Orange with White |
| 3 | Green with White |
| 4 | Brown with White |

Electrical Parameters:

| | |
|---------------------------|--------------------------------|
| Mutual Capacitance: | 14 pF/ft nominal |
| Capacitance Unbalance: | 330 pF/ft maximum |
| Velocity of Propagation: | 70% |
| Max. Conductor D.C.R.: | 28.6 ohm/1000 feet |
| Max. DCR Unbalance: | 5% |
| Max. Delay Skew: | 45.0 ns/100m |
| Characteristic Impedance: | from 0.772 - 100 MHz 100 ± 15% |
| | from 101 - 250 MHz 100 ± 22% |

Technical Details

Temperature Rating

| | |
|--------------------|----------------------|
| Installation | 0°C to 50°C |
| Operation | -10°C to 60°C |
| Nominal Diameters: | Over Cat6: 0.275 in. |
| | Over Mess: 0.095 in. |
| | Major: 0.390 in. |

Standards

- ANSI/TIA/EIA 568C.2 Category 6

Codes & Listings

- Non Listed



MADE IN THE USA

Issue Date: 05/13
Revision: 0



Category 6 Flooded W/ Messenger Polyethylene Jacket

Made in the USA

Electrical Characteristics:

| Frequency | Return Loss | Attenuation | NEXT | PS-NEXT | ELFEXT | PS-ELFEXT | ACR | PS-ACR |
|-----------|-------------|-------------|---------|---------|---------|-----------|---------|---------|
| | dB | dB(100m) | dB | dB | dB | dB | dB | dB |
| MHz | Minimum | Maximum | Minimum | Minimum | Minimum | Minimum | Minimum | Minimum |
| 1 | 20.0 | 2.0 | 80.3 | 78.3 | 73.8 | 70.8 | 78.3 | 76.3 |
| 4 | 23.0 | 3.8 | 71.3 | 69.3 | 61.8 | 58.8 | 67.5 | 65.5 |
| 10 | 25.0 | 6.0 | 65.3 | 63.3 | 53.8 | 50.8 | 59.3 | 57.3 |
| 16 | 25.0 | 7.6 | 62.2 | 60.2 | 49.7 | 46.7 | 54.6 | 52.6 |
| 20 | 25.0 | 8.5 | 60.8 | 58.8 | 47.8 | 44.8 | 52.3 | 50.3 |
| 31.25 | 23.6 | 10.7 | 57.9 | 55.9 | 43.9 | 40.9 | 47.2 | 45.2 |
| 62.5 | 21.5 | 15.4 | 53.4 | 51.4 | 37.9 | 34.9 | 38.0 | 36.0 |
| 100 | 20.1 | 19.8 | 50.3 | 48.3 | 33.8 | 30.8 | 30.5 | 28.5 |
| 200 | 18.0 | 29.0 | 45.8 | 43.8 | 27.8 | 24.8 | 16.8 | 14.9 |
| 250 | 17.3 | 32.8 | 44.3 | 42.3 | 25.8 | 22.8 | 11.5 | 9.5 |

Preparation For Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.

Purchase at

LANshack

Sales@LANshack.com | 888-568-1230