







# QuickTrex Tactical Fiber Optic Assemblies

## Optional Deployable Schill Reels

Reel SKU	Main Features and Specifications
<b>GT 235</b> 	Unbreakable synthetic rubber & heavy-duty steel construction, high-quality fittings, and spool brake.  Flange Diameter: 235 mm / 9.25 in Core Diameter: 135 mm / 5.31 in Spool Width: 110mm / 4.33 in Weight: 1kg / 2.1 lbs
<b>GT 310</b> 	Unbreakable synthetic rubber & heavy-duty steel construction, high-quality fittings, and spool brake.  Flange Diameter: 310 mm / 12.2 in Core Diameter: 170 mm / 6.69 in Spool Width: 132 mm / 1.5 in Weight: 1.6 kg / 3.5 lbs
<b>GT 380</b> 	Unbreakable synthetic rubber & heavy-duty steel construction, high-quality fittings, and spool brake.  Flange Diameter: 380 mm / 14.96 in Core Diameter: 236 mm / 9.29 in Spool Width: 182 mm / 7.17 in Weight: 3.9 kg / 8.6 lbs
<b>GT 450</b> 	Unbreakable synthetic rubber & heavy-duty steel construction, high-quality fittings, and spool brake.  Flange Diameter: 445 mm / 17.52 in Core Diameter: 296 mm / 11.65 in Spool Width: 187 mm / 7.36 in Weight: 5.1 kg / 11.3 lbs
<b>HT 485</b> 	Heavy-duty steel construction, high-quality fittings, spool brake, and folding crank.  Flange Diameter: 460 mm / 18.11 in Core Diameter: 178 mm / 7.01 in Spool Width: 210 mm / 8.27 in Weight: 7.2 kg / 15.9 lbs
<b>SK 4813</b>  Optional Dolly	Industrial-duty steel frame & drum flanges, glassfiber-reinforced polycarbonate core, stackable, high-quality fittings, spool brake, folding crank, blank hub cover for you own modifications, and available with optional heavy-duty dolly.  Flange Diameter: 460 mm / 18.11 in Core Diameter: 240 mm / 9.4 in Spool Width: 504 mm / 19.84 in Weight: 22 kg / 48.5 lbs